

DIGITAL AC CLAMP METER

C-LOGIC 80



- ❑ Power Supply : 1×9V 6F22 Battery
- ❑ Display 2000 counts
- ❑ Jaw Opening Φ 50mm/2.0"
- ❑ Continuity Buzzer <100 Ω
- ❑ Data Hold
- ❑ Low Battery Display
- ❑ Product Size :
235mm×96mm×46mm/9.25"×3.8"×1.8"
- ❑ Product Weight : 268g/0.59lb
- ❑ Certification : CE / ETL / RoHS
- ❑ Safety Rating : CAT II 1000V/ CAT III 600V

CONTENTS



C-LOGIC 80

DIGITAL AC CLAMP METER

General	
Power Supply	1×9V 6F22 Battery
Product Size	235mm×96mm×46mm/9.25"×3.8"×1.8"
Product Weight	268g/0.59lb
Certificate	CE/ETL/RoHS
Safety Rating	CAT II 1000V/ CAT III 600V

Specs	
Display Counts	2000
Jaw Opening	Φ50mm/2.0"
Continuity Buzzer	<100Ω
Data Hold	✓
Low Battery Display	✓

C-LOGIC 80

DIGITAL AC CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	1000 V	1 V	$\pm(0,8\%+3)$
AC Voltage	750 V	1 V	$\pm(1,2\%+5)$
AC Current	200 A	0,1 A	$\pm(2,5\%+5)$
	1000 A	1 A	$\pm(3\%+10)$
Resistance	200 Ω	0.1 Ω	$\pm(1\%+5)$
	20 K Ω	10 Ω	$\pm(1\%+8)$
Insulation test	20 M Ω	10 K Ω	$\pm(2\%+2)$
	2000 M Ω (<500M Ω)	1 M Ω	$\pm(4\%+2)$
	2000 M Ω (>500M Ω)	2 M Ω	$\pm(5\%+2)$

Product Code Information

SKU	CLOGIC80CBINT
EAN code	8435394776712
UPC code	810053671184
Pcs/export carton	20