

34XR-A

Display	LCD, 3999 digiti	
Tensiune CA	0,1 mV...750 V	$\pm(1,2\% \text{ rdg} + 8 \text{ digiti}) @ 45 \text{ Hz} \dots 2 \text{ kHz}$
Tensiune CC	0,1 mV...1000V	$\pm(0,1\% \text{ rdg} + 1 \text{ digit}) @ 10 \text{ M}\Omega$
Curent CA	0,1 μA ...10A	$\pm(1,5\% \text{ rdg} + 8 \text{ digiti}) @ 45 \text{ Hz} \dots 1 \text{ kHz}$
Curent CC	0,1 μA ...10A	$\pm(1,0\% \text{ rdg} + 1 \text{ digiti})$
Rezistenta	0,1 Ω ...40 M Ω	$\pm(1\% \text{ rdg} + 4 \text{ digiti})$
Continuitate	R < 35 Ω	
Ciclu de lucru	0..90%	$\pm(2,0\% \text{ rdg} + 5 \text{ digiti})$
Frecventa	10,00 Hz...1 MHz	$\pm(0,1\% \text{ rdg} + 3 \text{ digiti})$
Capacitanta	4,000 nF...4,000 mF	$\pm(5\% \text{ rdg} + 10 \text{ digiti})$
Temperatura	-20°C...1000°C	$\pm(2\% + 4^\circ\text{C})$
Clasa	CAT III/600V, CAT II/1000V	
Certificare	EN 61010, IEC 61010	
Baterie	1 x 9V	
Dimensiuni	196 x 92 x 60 mm.	
Greutate	~ 400 g. (incl. baterie)	