

### Chauvin Arnoux F200 Series

Model	F201	F203	F205
Diametru de prindere	34 mm		
Display	LCD	LCD cu iluminare din spate	
Rezolutie	6,000 digits		
Nr. valori afisate	1		
Tip achizitie	TRMS (AC)	TRMS (AC)/DC	TRMS (AC, AC+DC)/DC
Autogama	DA		
Detectie Automata AC/DC		DA	
AAC	0.15 pana la 600 A (varf 900A)		
ADC		0.15 pana la 900A varf	
AAC+DC			0.15 pana la 600A (varf 900A)
Precizie	1% citire + 3cts		
V AC	0.15 pana la 1,000 V (varf 1,400 V)		
V DC	0.15 pana la 1,400 V		
V AC+DC			0.15 pana la 1,000 V (varf 1,400V)
Precizie			1% citire + 3cts
Hz	Curent: 5.0 Hz pana la 3,000 Hz Tensiune: 5.0 Hz pana la 20.00 kHz		
Ohm	0.1 Ω pana la 59.99 kΩ		
Voltaj circuit deschis	≤ 8 V		
Masurare curent	≤ 680 μA		
Continuitate audio	DA		
Prag continuitate	Ajustabil de la 1 la 599 Ω		
Test dioda	DA		
Temperatura (tip K)	°C: -60.0 pana la + 1,000.0 °C		
Valori putere faza singulara si trifaza totala	DA		
Putere activa			1 w PANA LA 600 Kw
Putere reactiva			1 var pana la 600 kvar
Putere aparenta			1 VA pana la 600 kVA
FP / DPF			DA/NU
Armonice	DA		
THDf / THDr	DA/DA		
Analiza frecventa	NU		
Faza de rotatie (metoda celor 2 fire)	DA		